

FORMPOLY® N66GF25FRP

(25% Glass Fibre Reinforced Nylon66- Meets UL94 V0)

GENERAL

FPL offers a range of Nylon66 grades from unfilled, glass fibre reinforced, mineral reinforced to flame retardant including **FORMPOLY® N66GF25FRP**, which is heat stabilized, lubricated Glass Fibre Reinforced Nylon 66 with excellent mechanical / thermal properties and reduced shrinkage.

FORMPOLY® N66GF25FRP

Meeting UL-94 V0 flammability
Halogen Free FR
Warpage to free moulding
Good surface finish and Gloss
Good mechanical and electrical properties
High ESCR
Available in Black and Grey (RAL 7011 & 7016) colours

PRE-DRYING

FPL grades can normally be taken for direct processing. However, in case the material is exposed to atmosphere, it is advisable to pre-dry the material at 100 °C for 2 to 3 hours for good surface finish.

PACKING

FORMPOLY® N66GF25FRP is supplied in 25 Kg dry, ready to mould, in sealed bags to prevent the uptake of moisture.

APPLICATION

Electrical switches
MCB Housing
Relay Base
PCB Frames
Connectors

Property	ASTM Method	Unit	Value
Tensile Stress	D638	MPa	160
Elongation at Break	D638	%	3
Flexural Strength	D790	MPa	210
Flexural Modulus	D790	MPa	8000
Izod Impact Strength Notched	D256	kg cm/cm	13
Heat Deflection Temp - at 18.5 kg/cm ² load	D648	°C	248
Specific Gravity	D792	-	1.33
Volume Resistivity	D257	Ohms-cm	10 ¹⁵
Surface Resistivity	D257	Ohms	10 ¹⁴
Flammability @1.6mm	UL94	-	V0
Comparative Tracking Index	IEC 60112	V	600

Conditioned test specimen. All results are measured under Dry-as-moulded natural test specimen Coloured grades would record slightly lower mechanical properties as permitted by ASTM D-4066

The information present here is for general guidance. It is given in good faith but no warrant is attached

FORMULATED POLYMERS LIMITED

Manufacturers of Engineering Plastics Compounds

Ph: +91-44-26811236,7:: Fax:26811275 E Mail: info@formulatedpolymers.com

URL: www.formulatedpolymers.com

HO & Works: 59, SIDCO Industrial Estate, Thirumazhisai, Chennai - 600 124 India.

ISO 9001:2015, IATF 16949: 2009 & ISO 14001: 2015 Certified Firm

